

## SHSCam – standard sensor head overview

Type	AR-S	AR2	HR2	SHR-S	SHR4	UHR2	XHR2**
Detection area / mm <sup>2</sup>	4.8 x 3.6	4.8 x 3.6	11.2 x 7.0	10.3 x 8.5	10.3 x 10.3	15.1 x 15.1	36.4 x 27.6
Lateral resolution(s) / microlenses	32 x 24 37 x 28	43 x 32 71 x 53	85 x 53 125 x 79	69 x 57	79 x 79 117 x 117	101 x 101 116 x 116	331 x 251
Greyscales / Bit	12	12	12	8	12	12	12
Camera Bus	GigE	GigE	GigE/USB3.0	CameraLink	GigE/USB3.0	GigE	GigE
Sensor head dimensions (L x W x H) / mm <sup>3</sup>	64 x 36 x 36	64 x 36 x 36	GE: 65 x 29 x 29 U3: 53 x 29 x 29	55 x 60 x 60	GE: 65 x 29 x 29 U3: 53 x 29 x 29	60 x 50 x 50	59.2 x 60 x 60
Weight / kg	0.1	0.1	0.1	0.3	0.1	0.2	0.32
Evaluation Rate (typical) / Hz	50	30	20 14	30 Full Frame, >1000 on central ROI*	3	6	~1

\* For evaluation with DLL-based software

\*\* Wavelength range 375 – 900nm

- Default optimization wavelength for standard sensors is 635nm. Others from 405 – 1064nm are available. For optimization wavelengths in the UV range please ask.
- Recommended wavelength range for high precision measurements is optimization wavelength +/- 10%. Usable wavelength range is 405 – 1064nm.